Coloring Excellence – Providing Total Paint Solutions



INSPIRA DURAPLAST TEXTURE

Godavri Paint's Inspira Duraplast is a textured exterior wall paint that gives a durable decorative stone finish of uneven patterns and non-symmetrical designs, beautifying & protecting buildings for years. Inspira Duraplast is a combination of the strong and adhesive features of synthetic plaster and the decorative quality of paint. It brings the natural textures to the walls giving them an aesthetic look. It is a low VOC product. Inspira Duraplast is specially formulated out of Acrylic Polymers, Marble chips, Quartzpowder, Siliceous aggregates.





TECHNICAL DATA

Area Of Application Masonary walls, Fiber board,

RCC

Method Of Application Trowel

Consistency Paste with marble chips and sand

Finish Scratch like

Recommended Thinner Potable Water

Viscosity 300 to 400 units on penetrometer

Drying Time Surface dry: 2 hours

Hard Dry: Minimum 8 Hours

Coverage 2 sqft - 3 sqft per kg / 1 coats

"Actual coverage may vary to the quoted coverage due to factors like skill, surface porosity, tools, site conditions etc"

Dilution by Volume 2% to 5%

Film Thickness 1.5mm to 2 mm per coat

Packing 25 Kg

PRODUCT APPLICATION

SURFACE PREPARATION

Washing - Clean the surface which has to be painted with coir brush and water and ensure that it is free from any loose paint dust, grease and growth of algae, fungus or moth.

Surface imperfections - If any like cracks, holes, loose plaster etc should be repaired using white cement and fine sand in proper proportion to stop leakage or seepage in

Precautions - Do not apply the product if surface is subjected to continuous dampness / Seepage even after due surface preparation.

APPLICATION

- Stir the content thoroughly before opening
- Dilute the material as stated in the technical data
- Apply 1st coat of Godavri Exterior Primer (Optional)
- Apply 1 Coat of Inspira Duraplast with trowel
- Apply 2-3 Coats of Desired Paint for best result



SAFETY FEATURES

- Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- Keep out of reach of children and away from food, drink.
- May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- Wear eye protection during application.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of skin contact immediately wash skin with soap and plenty of water.
- Get medical attention if irritation develops or persists.
- Do not breathe vapour or spray.
- It is recommended to wear suitable nose pad during sanding and surface preparation to avoid -dust inhalation.
- Do not pour leftover paint down the drain or in water courses.
- In the event of spills, contain spillage using sand or earth.
- No added Lead, Mercury or Chromium compounds.

TECHNICAL AID SERVICE PROVIDED ON REQUEST





Manufactured by

GODAVRI PAINTS PVT. LTD.

Admin Office: Tulsiram Gupta Mills Estate, Darukhana, Reay Road, Mumbai 400010

For Customer Care contact: 022 23721249

admin@godavaripaints.com www.godavaripaints.com